

35-Ton Lowboy - SG



1-YEAR WARRANTY

NATIONWIDE SERVICE



35-Ton, 2 Axle, Detachable Non-Ground Bearing, Lowboy Trailer

This Specification is for a Model GTBN352-45-24-SG, 35-Ton, 2 Axle, Detachable Non-Ground Bearing, Lowboy Trailer. Max Payload is 70,000 lbs in 16' Load Concentration and a Shipping Weight of 15,800 lbs +/- 3%.

Overall Length:	45' 3" (543")	Main Beam:	16" @ 67 "1" beam main frame.
Overall Width:	8' 6" (102")	Cross Member:	8" Jr. "1" beams on 24" Centers.
Gooseneck:	10' 11" (131")	Side Rails:	12" channel side rail.
Swing Clearance:	86"	Rear Tail:	14" @ 43 "1" beam.
Load well Length:	24' (288")	Axles:	Two (2) ea 25,000 lbs capacity axles.
Rear Deck:	10' 4" (124")	King Pin:	2" heavy duty.
5th Wheel Height:	50"	Tires:	8 ea 255/70R x 22.5 "H" load range, steel belted radials.
King Pin Setting:	16"	Wheels:	8 ea. 8.25 x 22.5, 10 hole hub piloted steel disc wheels.
Ground Clearance:	8"	Brakes:	16.5 x 7 air brakes w/ spring parking brake on front axle Auto slack adjusters, & 2S1M ABS system on 2nd axle.
Deck Height:	24"		
Axle Spacing:	49"		

LOWBOY

Suspension:	Tandem spring ride suspension, 25K rated spings.
Front Ramps:	31" double hinged front loading flip ramps with grousers.
Rear Tail Section:	Open wheel with boom & bucket well.
Electrical:	12-Volt electrical system, 7 way SAE connector, All lights LED mounted in rubber grommets to DOT standards.
Hydraulics:	Wet line hook-up on trailer for tractor PTO operation.
Operating Pressure	Wet kit system requires 3000PSI at 10 GPM maximum flow to lift load at full capacity.
Decking:	2" oak flooring, open center, secured to frame with 5/16" self-taping torque screws.
Tie Downs:	14 ea "D" Ring tie downs 6 ea side on main deck, 1 on rear deck.
Out Riggers:	28 ea removable outriggers with double up front and double in middle of load well, 14 ea Side.
Finish:	Powdercoated to color of choice

Oficina Comercial: Badajoz 100 Of. 1117 - ☎ +56 (2) 32026730 - 📱 +56 (9) 78465444